

### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### **Listing of Claims:**

1. (Currently Amended)      A dye container for storing a hair dye, comprising:

a dye-containing space for preventing contact between hair dye remaining in the dye container and filling air introduced into the dye container by discharging the hair dye, the dye-containing space being defined in a collapsible thin resin film; and

at least one mouth disposed outside the dye-containing space, ~~adapted so that~~ the hair dye ~~being~~ discharged through the at least one mouth by an outside negative pressure applied at the at least one mouth.

2. (Previously Presented)      The container as set forth in claim 1, further comprising at least one hole formed at an outside of the dye container and adjacent to the dye-containing space so that an inside negative pressure created by diminution of the hair dye is reduced.

3. (Currently Amended)      A hair dyeing device for discharging dye by means of electric power to dye hair, comprising:

a main body having an electric motor, an electric power source, a switch, and a dye inlet port formed so that at least one dye container is attached to the main body through the dye inlet port, the at least one dye container discharging dye through the dye inlet port by ~~[[a]]~~ an outside negative pressure applied at the dye inlet port;

a comb assembly attached to the main body, the comb assembly comprising a plurality of tines, each of the tines having at least one flow channel formed therein;

at least one pump connected to the dye inlet port and powered by the electric motor for supplying dye from the at least one dye container to the tines, the at least one pump ~~applying the~~

providing the outside negative pressure ~~at the dye inlet port~~; and

a plurality of flow channels formed so that the dye discharged from the dye inlet port ~~supplied by the at least one pump~~ flows to the respective tines along the corresponding flow channels.

4. (Original) The device as set forth in claim 3, wherein the comb assembly is pivotably attached to one end of the main body.

5. (Original) The device as set forth in claim 3, wherein each of the tines of the comb assembly has one to eight flow channels formed therein.

6. (Previously Presented) The device as set forth in claim 3, wherein the at least one pump is a multi channel pump having a plurality of pumping elements divided by partitions, the pumping elements being coaxially arranged, and wherein the number of the pumping elements corresponds to that of the tines.

7. (Previously Presented) The device as set forth in claim 3, further comprising a valve mounted in each of the flow channels formed between the at least one pump and the comb assembly so that the dye is discharged through each of the flow channels while the dye is mixed with another dye or the dye is discharged through each of the flow channels while the dye is not mixed with another dye depending upon selected positions of the valve.

8. (Previously Presented) The device as set forth in claim 3, further comprising an intermediate plate attached to the dye inlet port so that the at least one dye container is easily replaced irrespective of the size of a mouth of the dye container.

9. (Previously Presented) The device as set forth in claim 3, further comprising a plurality of dispensers disposed between the at least one pump and the comb assembly for uniformly distributing the dye supplied by the at least one pump, wherein each of the dispensers has a plurality of rotors arranged on a same shaft.